

Nastri strutturati											
Prodotto e colore		Durezza in Shore	Gamma temperature	Coefficiente di frizione su acciaio (sotto)	Spessore	Minimo diametro di puleggia			Forza di trazione: pretensione all'1%		Certificazioni
						mm	mm	Inch	kg/cm	lbs/in	
ITO 50	FELB - ITO50	80A	-40° C to 50° C -40° F to 120° F	0.45	2	12	1/2	0.32	1.87	FDA/ EU	
					2.5	15	9/16	0.40	2.32		
					3	18	11/16	0.50	2.80		
	FELW - ITO50	80A	-40° C to 50° C -40° F to 120° F	0.45	2	12	1/2	0.32	1.87	FDA/ EU	
					2.5	15	9/16	0.40	2.32		
					3	18	11/16	0.50	2.80		
	FMB - ITO50	95A/46D	-30° C to 60° C -20° F to 140° F	0.36	2.5	35	1 3/8	1.50	8.40	FDA/ USDA/ EU	
	FEMB - ITO50	95A/46D	-30° C to 60° C -20° F to 140° F	0.25	2	30	1 3/16	0.60	3.36	FDA/ USDA/ EU	
					2.5	35	1 3/8	0.74	4.20		
					3	40	1 5/8	0.94	5.26		
	FEMW - ITO50	95A/46D	-30° C to 60° C -20° F to 140° F	0.25	2	30	1 3/16	0.60	3.36	FDA/ USDA/ EU	
					2.5	35	1 3/8	0.74	4.20		
					3	40	1 5/8	0.94	5.26		
	FHW - ITO50	59D	-20° C to 75° C -5° F to 170° F	0.28	2	70	2 3/4	1.50	8.40	FDA/ USDA/ EU	
					2.5	80	3 1/8	2	11.20		
					3	90	3 1/2	2.50	14		
	ITR10	FELW - ITR10	80A	-40° C to 50° C -40° F to 120° F	0.45	3	18	11/16	0.50	2.80	FDA/ EU
						4	25	1	0.70	3.92	
IRT	FELB - IRT	80A	-40° C to 50° C -40° F to 120° F	0.45	4	25	1	0.60	3.40	FDA/ EU	
	FEMB - IRT	95A/46D	-30° C to 60° C -20° F to 140° F	0.25	3.5	40	1 5/8	1	5.60	FDA/ USDA/ EU	
					4	55	2 3/16	1.20	6.80		
	FMB - IRT	95A/46D	-30° C to 60° C -20° F to 140° F	0.36	3.5	52.5	2 1/8	2.10	11.80	FDA/ USDA/ EU	
					4	60	2 3/8	2.40	13.50		
Spikes*	FELB - SP	80A	-40° C to 50° C -40° F to 120° F	0.45	2	20	1 3/16	0.40	2.24	FDA/ EU	
					2.5	24	1 5/16	0.50	2.80		
					3	28	1 1/8	0.60	3.36		
	FEMB - SP	95A/46D	-30° C to 60° C -20° F to 140° F	0.25	2	40	1 5/8	0.80	4.50	FDA/ USDA/ EU	
					2.5	45	1 3/4	1	5.60		
					3	50	2	1.20	6.80		
	FEMW - SP	95A/46D	-30° C to 60° C -20° F to 140° F	0.25	2	40	1 5/8	0.80	4.50	FDA/ USDA/ EU	
					2.5	45	1 3/4	1	5.60		
					3	50	2	1.20	6.80		
Crescent Top	FELB - CT	80A	-40° C to 50° C -40° F to 120° F	0.45	3	35	1 3/8	0.60	3.36	FDA/ EU	
	FMB - CT	95A/46D	-30° C to 60° C -20° F to 140° F	0.40	3	60	2 3/8	1.80	10.12	FDA/ USDA/ EU	
	FEMB - CT			0.25	3	60	2 3/8	1.20	6.75		
	FEMW - CT			0.25	2.5	50	2	1	5.60		
Mini Cleats	FELB - MC	80A	-40° C to 50° C -40° F to 120° F	0.45	2.5	40	1 5/8	0.50	2.80	FDA/ EU	
	FELW - MC	80A	-40° C to 50° C -40° F to 120° F	0.45	2.5	40	1 5/8	0.50	2.80	FDA/ EU	
					3	50	1 5/8	0.60	3.40		
FEMB - MC	95A/46D	-30° C to 60° C -20° F to 140° F	0.25	3	70	2 3/4	1.20	6.80	FDA/ USDA/ EU		

**Note: Spikes** - \*L'altezza delle punte rispetto la base è di 2.8mm