


**TSV1304**

**2FR8 V7/V7 M B**



Belt construction informations	
Conveying side material	PVC 73ShA
Conveying side surface	Matt
Conveying side property	/
Conveying side color	Blue
Traction layer (material)	Polyester (PET)– Rigid
Number of Fabrics	2
Pulley side material	PVC
Pulley side surface	Negative Pyramid
Pulley side property	/
Pulley side color	Blue

Special characteristics	
Antistatic	No
Joining method	Single Z
Flammability	No specific property
Food suitability, FDA	Yes
Food suitability, USDA	Yes
Food suitability, EU	Yes- acc. to 1935/2004 No.10/2011
Other features	Carotene resistant

Technical data		
Thickness of belt	3,1 mm	0,12 inch
Mass of belt (beltweight)	3,7 kg/m <sup>2</sup>	0,75 Lb/ft
Tensile force for 1% elongation (k1% static) per unit of width	8 N/mm	46 lbf/in
Min. operating temperature admissible (continuous)	-5 °C	23 °F
Max. operating temperature admissible (continuous)	80 °C	176 °F
Max. production width	2000 mm	78,74 inch
Pulley diameter (minimum)	60 mm	2,36 inch
Pulley diameter in counter flection (minimum)	60 mm	2,36 inch

*DISCLAIMER: the information contained in this document describes the features of the MOTECH product as tested in a laboratory environment at a temperature of +23°C at 50% relative humidity (DIN 50005/ISO 554). It does not necessarily reflect the conditions of industrial use and it does not guarantee the product to be suitable for certain applications. The client remains liable for the proper selection and correct use of the MOTECH product. MOTECH cannot be held responsible should damages arise from the use of its products. Necessary alterations to this data can be made without prior notice*