



TSV0684

3GF14 U0/V8 V A

| Belt construction informations | |
|--------------------------------|-----------------------|
| Conveying side material | PVC-74ShA |
| Conveying side surface | Smooth |
| Conveying side property | / |
| Conveying side color | Petrol Green |
| Traction layer (material) | Polyester- Flexible |
| Number of Fabrics | 3 |
| Pulley side material | Polyurethane (PU) |
| Pulley side surface | Impregnated PU fabric |
| Pulley side property | / |
| Pulley side color | White |

| Special characteristics | |
|-------------------------|----------------------|
| Antistatic | Yes |
| Joining method | SingleZ |
| Flammability | No specific property |
| Food suitability, FDA | No |
| Food suitability, USDA | No use intended |
| Food suitability, EU | No |
| Other features | / |

| Technical data | | |
|--|-----------------------|-------------|
| Thickness of belt | 3,8 mm | 0,15 inch |
| Mass of belt (beltweight) | 4,6 kg/m ² | 0,92 Lb/ft |
| Tensile force for 1% elongation (k1% static) per unit of width | 14 N/mm | 80 lbf/in |
| Min. operating temperature admissible (continuous) | -10 °C | 14 °F |
| Max. operating temperature admissible (continuous) | 70 °C | 158 °F |
| Max. production width | 3000 mm | 118,11 inch |
| Pulley diameter (minimum) | 120 mm | 4,72 inch |
| Pulley diameter in counter flection (minimum) | 140 mm | 5,51 inch |

DISCLAIMER: the information contained in this document describes the features of the MOTECH product as tested in a laboratory environment at a temperature of +23°C at 50% relative humidity (DIN 50005/ISO 554). It does not necessarily reflect the conditions of industrial use and it does not guarantee the product to be suitable for certain applications. The client remains liable for the proper selection and correct use of the MOTECH product. MOTECH cannot be held responsible should damages arise from the use of its products. Necessary alterations to this data can be made without prior notice