



TSV1276

2 GR8 U0/U10 LG V A

Belt construction informations	
Conveying side material	Polyurethane(PU)-73
Conveying side surface	Longitudinal grooves
Conveying side property	/
Conveying side color	Green
Traction layer (material)	Polyester (PET)- Rigid
Number of Fabrics	2
Pulley side material	Polyurethane (PU)
Pulley side surface	Impregnated PU fabric
Pulley side property	No noise
Pulley side color	White

Special characteristics	
Antistatic	Yes
Joining method	Single Z
Flammability	No specific property
Food suitability, FDA	No
Food suitability, USDA	No
Food suitability, EU	No
Other features	/

Technical data		
Thickness of belt	2,3 mm	0,09 inch
Mass of belt (beltweight)	2,3 kg/m ²	0,471 Lb/ft
Tensile force for 1% elongation (k1% static) per unit of width	6 N/mm	34,26 lbf/in
Min. operating temperature admissible (continuous)	-30 °C	-22 °F
Max. operating temperature admissible (continuous)	100 °C	212 °F
Max. production width	1400 mm	55,12 inch
Pulley diameter (minimum)	24 mm	0,9 inch
Pulley diameter in counter flection (minimum)	60 mm	2,4 inch

DISCLAIMER: the information contained in this document describes the features of the MOTECH product as tested in a laboratory environment at a temperature of +23°C at 50% relative humidity (DIN 50005/ISO 554). It does not necessarily reflect the conditions of industrial use and it does not guarantee the product to be suitable for certain applications. The client remains liable for the proper selection and correct use of the MOTECH product. MOTECH cannot be held responsible should damages arise from the use of its products. Necessary alterations to this data can be made without prior notice